



3





5

"Keeper Well" options.



- Long string of 9-7/8" x 7" casing is again the primary option...
 - Cement simulations indicate it is possible to obtain a successful cement job.
 - It is possible to fulfill MMS regulations of 500' of cement above top HC zone (thought to be 17,803')
 - Some risk, if losses occur, to have and open annulus to wellhead, with HC zone(s) open to 9-7/8" seal assembly as only barrier.
 - Potential need to verify TOC with USIT log and perform remedial cement job prior to TA if losses occur during cement job. May also need to obtain a BP / MMS dispensation for TOC.
 - Best economic case and well integrity case for future completion operations.

"Keeper Well" options.



- 7" Liner (with 7" x 9-7/8" XO x 11-7/8" Versaflex hanger) is now the contingency option...
 - Use this option if losses or hole stability problems occur during the conditioning run with 8-1/2" bit and bha.
 - Less issue with landing it shallow (we can also ream it down)
 - Can run it to bottom, if bridge at 18,280' seen during logging reappears.
 - Liner hanger acts as second barrier for HC in annulus if losses occur during cement job.
 - Primary cement job has slightly higher chance for successful cement lift due to lower ECD.
 - Remedial cement job, if required, easier to justify to be left for later due to liner top seal acting as second barrier.

"Keeper Well" options.



- Plug open hole and TA well (least preferred, but still an option if hole conditions go south)
 - Minimizes today's dollars and NPT exposure.
 - All primary well objectives have been achieved.
 - Increases cost to completion by \$10 \$15 MM+ for drilling plugs, re-drilling production hole, re-logging.

8

