11300 1112JDK

15 OCT 1987

From: Commander, Atlantic Division, Haval Facilities Engineering Command To: Commanding Gameral, Harine Corps Base, Camp Lejeune

Subj: EMERGENCY CENERATOR, STRAM PLANT HP1700

Ref: (a) Heeting MCB Camp Lejeune (Utilities Personnel)/LANTHAVFACRHGCOM (Mr. David Knight/Mr. Joe Belice) of 20 May 1987

(b) Facility Project LR317M Replace Goal Feeders and Pulverizers, Steen Plant, Building HP1700

(c) NAVFAC Design Manual DH-3.6

acl: (1) Equipment to be Operated by Generator

(2) Cost Estimate for Emergency Generator Installation at Maval Amphibious Base, Little Creek

- 1. During reference (a) the method of operation of the central steam plant, HP1700, during an electrical power outage was discussed. In the past the procedure was to bring on line the existing 20 KW emergency generator, switch to oil firing and operate the boilers with natural draft. A purge cycle is required to eliminate any combustible gasses that may remain in the furusco box after a loss of ignition. The new control system, which was installed as part of reference (b), is programmed for a five minute purge cycle before ignition. During a loss of power this will cause a loss of some steam pressure that is required for operation of sumiliaries such as the feed water pumps. Operational personnel requested that a by-pass be provided so that this five winute delay for purging could be eliminated during a power outage. It was agreed that a switch, even a keyed switch, that would eliminate the purge cycle during lose of power was not a good alternative because of the obvious safety problems. It was also agreed that a natural draft purge is not sufficient. A forced draft purge is required. Reference (b) is also providing an additional 100 KW generator that will serve the ignition oil pump, new controls, No. 6 oil pump and the electrostatic precipitator dampers.
- 2. To eliminate the safety problem of starting a boiler with a limited purge cycle and to provide essential steam to facilities it is recommended that the existing emergency generators be replaced with one emergency generator capable of operating the assential plant equipment.
- 3. Reference (c) also recommends that steam plants be equipped with an emergency generator with enough capacity to allow essential equipment operation. To supply essential steam during the coldest winter months at least two boilers must be on line. The estimated size of a generator to operate two boilers at HP1700, firing oil, is 750 KW, as shown on enclosure (1).

The Carlo Kalgoring Los Delicel of CO. 100 Partended Personal Property Co.

pasty errorisoring ten ereteen feet sonique atien, applete villing (a)

Plane Julities Briyon est-mademan as the SWAN (2)

(1) Equipment to the distribution of the company of

provided and to arthe en line the retains of the congress, to the provided to the last of the congress of the conference as start carry A . These is rules asir enalled and sintene the guit 19 Ite of winder the face matern aldfacother was ecretatin of texture To the Little and and the covered or seed which was leastlined to the act of reference (e), by programming and a live manufactor programming to the restricted to the second of power this will cause a long to the restrict of the feet water Lines pe boll of as accept a rada besemper demonstrate desired. La second de la constant de la c The Street of th the belonger and water this local account which he be the filler

Picts as controls, No. v att prop sid the closicolatio processed dampier the second of the second secon

the rest became made at the chilitan of one to refine an array by calables everyency constant to replace to becaling the constant paragraph

as delection to be recommended attack attack of a language of a language of ipanifone felicines were or withput but tone hite yes these tone The action desire included and artists made a linear light of the responsition of ideas ... we well not read to the same the same that the same of a confidence to water the first of the second of the second second of the Subj: EMERGENCY GENERATOR, STEAM PLANT HP1700

- 4. It is suggested that a project be prepared to install a 750 KW generator in HP1700. Enclosure (2) is a detailed Government Cost Estimate for the installation of a 750 KW emergency generator at the central steam plant at the Naval Amphibious Base, Little Creek, as can be seen the estimated cost is \$272,000. This cost estimate contains some protective devices and equipment for operating the generator in parallel with the utility company, which you may not need. If the final scope of the project is over \$200,000, the project would require MILCON funding.
- 5. After the project has been submitted, and has the support of higher authority we recommend that a request for a Mobile Utility Support Equipment (MUSE) 750 KW diesel generator be forwarded to the Naval Energy and Environmental Support Activity (NEESA) via this Command and your major claimant. A MUSE diesel generator can provide the emergency support for the steam plant until the project is completed. To connect the MUSE generator to the plant some electrical work must be accomplished. If technical assistance is required, please contact this office.
- 6. Additionally, if you wish to operate the generator in parallel with the utility, contact LANTNAVFACENGCOM Code 11 so that Carolina Power and Light's requirements for parallel operation can be determined.

A. J. HANSEN By direction

Advance Copy to: MCB Camp Lejeune, Utilities Division

Blind Copy to: 403 1112 11S 09BS (w/o encl) Doc #7894A/msf A FEBRUARY WITH THE BOTHER TO THE STATE OF THE STATE

in the control of the control of the project of the project of the control of the

After the project is been ablitted, and has the north of bright addressing the project square of archar adjusting to the square of the square

S. Aldicionals, it can also to operate the generator to want to the contract of the contract o

kadmalis.com

Alva carbony to:

or voor I ma

DOC \$7874ALmer