11800 BOSM

FEB 1 0 1987

From: Assistant Chief of Staff, Base Operational Support Management Assistance

To: Donald R. Gurganus, Base Maintenance Division

Via: (1) Assistant Chief of Staff, Facilities &we 2/11/87 (2) Base Maintenance Officer

Subj: MODEL INSTALLATION PROGRAM PROPOSAL

Encl: (1) MIP #87-CLNC-045-FAC, Hydrostatic Testing of Unfired Pressure Vessels

1. This office is in receipt of your submission to the Model Installation Program, and has assigned it the number identified in the enclosure. The proposal is currently being staffed and processed. You will be notified as soon as a decision has been made.

2. We appreciate your participation in the Model Installation Program and ask for your continued support. Good ideas will make the Camp Lejeune community a better place to work and live.


H. F. SMITH

FEB 1 0 1987

Part Control As

Euc anist

Eme anna



INSTRUCTIONS:	DO NOT WRITE IN THIS SPACE	
1. COMPLETE ALL INFORMATION REQUESTED. 2. PLEASE PRINT OR TYPE LEGIBLY.	DATE RECEIVED	
3. USE ADDITIONAL SHEETS IF NECESSARY. 4. FORWARD COMPLETED PROPOSAL TO AC/S, BOSMAD, MCB	3 Feb 87 PROPOSAL NUMBER 87-CLNC-045-FAC	
TITLE OR SUBJECT OF PROPOSAL		
Hydrostatic Testing of Unfired Pressure Vessels		
NAME, TITLE, GRADE/RANK, UNIT OF SUBMITTER(S) Donald R. Gurganus, Transportation General Foreman, WS-13, Heavy Equipment Unit	PHONE 451-5909	

CURRENT PROCEDURE

Unfired Pressure Vessels, Air Compressors, are inspected on Marine Corps Base and New River Air Station in accordance with NAVFAC MO-324. They also have been and are hydrostatic tested at regular frequencies. The majority of this equipment has a working pressure from 15-250 psi.

PROPOSED PROCEDURE (If a directive/order must be waived to implement proposal-Identify the specific reference.) Request a waiver of NAVFAC MO-324 and abide by regulations as set forth in OSHA Safety and Health Standards, 29 CFR 1910, General Industry, Revised 11 March 1983, section 1910.169.

## BENEFITS/ADVANTAGES

Benefits and advantages would not require the internal nor the hydrostatic test. There are a minimum of 104 Air Receivers located on Marine Corps Base and New River Air Station. Significant amount of time is required to disassemble the plumbing, fill with water and to test these Air Receivers internally and hydrostatically. After the test has been conducted the plumbing has to be reconnected for use. This procedure in the past has required the assistance of the Tester/Inspector, Plumber, and an Electrician. While this test is in progress the using unit is unable to use the equipment until the test has been completed.

INTER UNDERSTAND THAT THE ACCEPTANCE OF A CASH AWARD FOR THE USE OF THIS PROPOSAL BY THE UNITED STATES GOVERNMENT SHALL NOT FORM THE BASIS OF A FURTHER CLAIM OF ANY NATURE UPON THE UNITED STATES BY ME (US), MY (OUR) HEIRS, OR ASSIGNS.


Januar 2-2-81 (SIGNATURE AND DATE)

(SIGNATURE AND DATE)

FNCL(1)

MODEL INSTALLATION PROPOSAL

**Excellent Installations — The Foundation Of Defense** 



OPNAV 5216/144A (Rev. 8-81) 5/N 0107-LF-052-2320

DEPARTMENT OF THE NAVY

Memorandum

MAIN

DATE: 0 4 MAR 1987

TO:

SUBJ:

FROM: Thomas Lanier, P&E Section

Director, Operations Branch

MIP #87-CLNC-045-FAC, HYDROSTATIC TESTING OF UNFIRED PRESSURE VESSELS

1. The Model Installation Proposal No. 87-CLNC-045-FAC covering hydrostatic testing of Unfired Pressure Vessels is addresed in the following paragraphs.

a. Unfired Pressure Vessels are potentially dangerous vessels and the procedures for inspection come under NAVFAC MO-324, December 1984, updated June 1986. Exception to these requirements will not be made without the formal concurrence of the NAVFACENGCOM Boiler Inspection Certification Board as per NAVFAC MO-324 Page 1-1.

b. The majority of air receivers have small openings (usually 1 1/2" pipe size or less) for internal inspection. Trying to determine the amount of corrosion and pitting inside the tank is poor at best. I beleive that a hydrostatic test every few years is the best way to safely say a tank is good for a specific working pressure. Most of the Unfired Pressure Vessels on Marine Corps Base Camp Lejeune and New River Air station operate at a pressure between 100-175 PSI. I recommend that the testing procedure for Unfired Pressure Vessels not be changed.

c. Being the Inspector of boilers and Unfired Pressure Vessels, I feel better about issuing a certificate to operate the unit if I have the option to hydrostatically test at my discretion.

1. L. Lanier

T. L. LANIER

Inomatic Lanier, P2C 2000

MIP 407-CLNC 045 FAG. HYDROSTATIC TESTING OF UNFIRED PRESSURE

 The Model Installation Proposal No. 87-CLNC-045-FAC Covering hydrostatic testing of Unfired Pressure Vessels is addresed in the following paragraphs.

a) Unfired Pressure Vessels are potentially dangerous vessels and the procedures for inspection come under NAVLAC MO-324. December 1984. undated dune 1986. Exception to these requirements will not be mede without the formal concurrence o the New AGENALCH BUTLEY Inspection Certification Hoard as per MAVEAC NO-324 Page 1-1.

b. The majority of air receivers have small openings (usually 1.1/2" pipe size or less) for internal inspection. Trying to determine the amount of corrosion and pitcing inside the tank is puch at best. I balarys that a hydrostatic test every fer years is the best way to safely say a tank is doed for a specific working project way to safely say a tank is doed for vessels on Marine Corps Base Camp Lejeune and New River Air station operate at a pressure between 100-175 PS1. I recommend that the testing projective for Unified Pressure Not be

Being the Inspector of builder and Unified Francis . I techniciter shout issuing a wertiff date to per-

DEPARTMENT OF THE NAVY

OPNAV 5216/144A (Rev. 8-81) S/N '0107-LF-052-2320

. 10

Memorandum 11800 FAC

DATE: FEB 1 9 1987

FROM: Assistant Chief of Staff, Facilities, Marine Corps Base, Camp Lejeune Race Maintenance Officer

TO: Base Maintenance Officer

SUBJ: MODEL INSTALLATION PROGRAM PROPOSALS

Ref: (a) AC/S BOSMAD memo 11800 BOSM dtd 10 Feb 87

- Encl: (1) MIP #87-CLNC-045-FAC, Hydrostatic Testing of Unfired Pressure Vessels
  - (2) MIP #87-CLNC-046-FAC; Reducing Water Pressure in Family Housing

1. Please review the enclosed MIP proposals in accordance with established procedures and reference (a). Response is requested by 6 March 1987.

Macafaulas direction

40011 Din.

AN OLIVER OF TO AN AND THE TRANSPORTED AND A COMPANIES OF THE COMPANIES OF THE 8 G 3. 1 C restaid estatetoist ser

HODEL HERVITAREON PROVINCE ENCLOSALE NOLE (51 ACV: 7050AP) NEWS 11100 ENCE 316 10 Pc 49

Facts ( ) at #7-CLUC-+ 5-DAC, Proroutatio Trating of Marine of Pleased anners!

(2) The + -- CLEC-- L-FEC, Release there are produced in Fally General Construction

. The setting the conteres with proposals to accordence with retuilened procetores and referring (a). Levices is recorded Street down

entestine Pv itestine

11800 BOSM FEB 1 0 1987

## MEMORANDUM

- From: Assistant Chief of Staff, Base Operational Support Management Assistance
- To: Assistant Chief of Staff, Facilities
- Subj: MODEL INSTALLATION PROGRAM PROPOSAL
- Encl: (1) MIP #87-CLNC-045-FAC, Hydrostatic Testing of Unfired Pressure Vessels
  - (2) MIP #87-CLNC-046-FAC, Reducing Water Pressure in Family Housing

1. Enclosures (1) and (2) are forwarded for review and comment. Request recommendation for approval or disapproval be returned to this office with an excerpt from the applicable directive within ten working days from date of receipt. Recommendation for disapproval should be accompanied by a written rationale.

2. This office will forward proposals recommended for approval directly to the Commanding General for decision. Proposals recommended for disapproval will be reviewed by the Model Installation Steering Committee prior to forwarding to the Commanding General.

3. It is recommended that any other Marine Corps Base department that may be affected by the approval or disapproval of the enclosed proposals be contacted during your review.

4. BOSMAD POC is D. Martin, 5521/1577.

H. F. SMITH

NETION PROVIDE

tent for the second of the the second stands approximation of the second s

Werteren out of seeit head there.

RATES OF BEET BEFORE OVER STATES AND AND AND AND AND AND

Charles of the state of the sta


13) AL STA-CLOC-011-D- Reducting Worker Presence in

1. Thological is fly down (2) and focultied for the same and competition hoggoard metry willing the special set limit that is a public to the special size of the state of the set of the special set of the lap weeking of a first set of special set of the special set of the approvel size of the second set of the state of the special set of the approvel size of the second set of the state of the state.

ຂີ່ ແລະ 10 ແລະນີ້ຄື ແລະ 10 b ປະສາຊີລະດີ ທີ່ເລັກນາທີ່ສະດີ ກາງການການແລະ ແລະ 20 ຫຼື ເຈັ້ມສູ່ມີເປັນເປັນການ ແລະ 10 ແມ່ນ ແລະ 10 ແມ່ນ 20 ແມ່ນ 20 ແມ່ນ 20 ແມ່ນ 20 ແມ່ນ ການສະມະນະ ແລະ 10 ແມ່ນ 20 ແມ່ນ 20 ໂດຍການ 20 ແມ່ນ 20 ແມ່ນ 20 ແມ່ນ 20 ແມ່ນ ທີ່ມີມີຊີລະດີ ເຊັ່ນການການ ທີ່ມີມີຊີລະດີ ເຊັ່ນການການ

and the provident of the second s Second s Second second





Hydrostatic Testing of Unfired Pressure Vessels	87-CLNC-045- FAC
NAME, TITLE, GRADE/RANK, UNIT OF SUBMITTER(S) Donald R. Gurganus, Transportation General Foreman, WS-13,	PHONE 451-5909
Heavy Equipment Unit	and a second second second second

CURRENT PROCEDURE

Unfired Pressure Vessels, Air Compressors, are inspected on Marine Corps Base and New River Air Station in accordance with NAVFAC MO-324. They also have been and are hydrostatic tested at regular frequencies. The majority of this equipment has a working pressure from 15-250 psi.

PROPOSED PROCEDURE (If a directive/order must be waived to implement proposal-Identify the specific reference.) Request a waiver of NAVFAC MO-324 and abide by regulations as set forth in OSHA Safety and Health Standards, 29 CFR 1910, General Industry, Revised 11 March 1983, section 1910.169.

BENEFITS/ADVANTAGES

Benefits and advantages would not require the internal nor the hydrostatic test. There are a minimum of 104 Air Receivers located on Marine Corps Base and New River Air Station. Significant amount of time is required to disassemble the plumbing, fill with water and to test these Air Receivers internally and hydrostatically. After the test has been conducted the plumbing has to be reconnected for use. This procedure in the past has required the assistance of the Tester/Inspector, Plumber, and an Electrician. While this test is in progress the using unit is unable to use the equipment until the test has been completed.


TO UNDERSTAND THAT THE ACCEPTANCE OF A CASH AWARD FOR THE USE OF THIS PROPOSAL BY THE UNITED STATES GOVERNMENT SHALL NOT FORM THE BASIS OF A FURTHER CLAIM OF ANY NATURE UPON THE UNITED STATES BY ME (US), MY (OUR) HEIRS, OR ASSIGNS.

12-2-81 (SIGNATURE AND DATE)

(SIGNATURE AND DATE)

MODEL INSTALLATION PROPOSAL

**Excellent Installations** — The Foundation Of Defense



## 11 MAR 1987

11800 MAIN

Base Maintenance Officer, Marine Corps Base, Camp Lejeune Assistant Chief of Staff, Facilities, Marine Corps Base

## MIP 87-CLNC-045-FAC

1. The heart of the problem is NAVFAC MO-324 that requires an internal inspection of unfired pressure vessels (UPV) not less than once every two years for any tank that has an operating pressure in excess of 15 PSI or a volume of more than five cubic feet. Many of the air compressors aboard Camp Lejeune fall into that requirement but have no openings sufficiently large enough to conduct an internal inspection. Accordingly, NAVFAC MO-325 states a hydrostatic pressure test (fill up with water and pressurize at 1.5 times the maximum working pressure) may be substituted for internal inspection. Hence, we are required to hydrostatically test these unfired pressure vessels because of no means to inspect internally. We concur with the MIP that this is an unnecessary frequency and unnecessary work.

2. It is suggested that the MIP be forwarded to NAVFACENGCOM via our Engineering Field Division (LANTDIV) for review to determine the following:

a. Are there satisfactory techniques for conducting internal inspections on UPV's that have very limited internal access?

b. Can the minimum thresholds (five cubic feet & 15 PSI) for UPV inspection requirements be adjusted upward?

c. Can UPV's in non-utility type applications be completely exempt from inspections? This would typically be shop type air compressors.

3. We feel the MIP has merit, but requires relief from existing Department of Navy directives, specifically NAVFAC MO-324. It is recommended relief be pursued.

#### C. G. POWELL

Blind copy to: Dir, Ops T. Lanier, P&E D. Gurganus, M&R MIP Files Writer: C. Powell, MAIN, X2511 Typist: S. Schmitz, 09 Mar 87

# 1 1 MAR 1987

MIPHER CONCEPTION

ALSIATER STATION STATE AND THE PLACE AND ALSO AND ALSO AND ALSO

1. Area hower from a contrained and ALL Work of the Suggethera are intermed in specification of the diarchera would be and the second of the second of the diarchera would be and the beaution of the second of the diarchera and the second of the break second of the second second of the diarchera and the feed. Again the second of the short second of the tester of the second free to the second of the second second of the second of th

er veen oo tet ee yo untur tar, man sian erla, een tar da, tar tar eti tureetia

The ATENIN'S GREEDEN MY LEVE VOITER DE THE CLEERE AND THE AT

Sate gentic mount of contemporations and the coeff with no

in the property of the second s

teri (automa egenerative) attra agrinada (j averida) anenentivoli (artra) De conduction (nteriore) interestivoli economicatori (contexterio) 282 metro de ese anenen contexterio metropicative (teriore) contexterio

Autoplation action action in the part in the most of a static factor is a static factor for the static factor is a static factor in the static factor in the static factor is a static factor in the static factor is a static factor in the static

Y Let a start the monthly different the short has first a start by the set of the start of th

 $d_{1}$  , we require the difference of the state of the term of the difference of the state of

nde ender sont tegensker periodikker for "Enderstanden". De en 299 s. und Jahre Vall, filmit og odjernati afgept".

and the second second

27

Blind Scov to: Dir, Ops T. Lanier, P&E D. Gurganus, M&R MIP Files Mriter: C. Powell, MAIN, X2511 Typist: S. Schmitz, 09 Mar 87

OPNAV 5216/144A (Rev. 8-81) S/N 0107-LE-052-2320

DEPARTMENT OF THE NAVY

Memorandum 11800 FAC

FEB 1 9 1987 DATE:

Assistant Chief of Staff, Facilities, Marine Corps Base, Camp FROM: Lejeune Base Maintenance Officer

TO:


MODEL INSTALLATION PROGRAM PROPOSALS SUBJ:

(a) AC/S BOSMAD memo 11800 BOSM dtd 10 Feb 87 Ref:

- (1) MIP #87-CLNC-045-FAC, Hydrostatic Testing of Unfired Encl: Pressure Vessels
  - (2) MIP #87-CLNC-046-FAC; Reducing Water Pressure in Family Housing

1. Please review the enclosed MIP proposals in accordance with established procedures and reference (a). Response is requested by 6 March 1987.

Maco Aoulos direction



11800 BOSM FEB 1 0 1987

MEMORANDUM

- From: Assistant Chief of Staff, Base Operational Support Management Assistance
- To: Assistant Chief of Staff, Facilities
- Subj: MODEL INSTALLATION PROGRAM PROPOSAL
- Encl: (1) MIP #87-CLNC-045-FAC, Hydrostatic Testing of Unfired Pressure Vessels
  - (2) MIP #87-CLNC-046-FAC, Reducing Water Pressure in Family Housing


1. Enclosures (1) and (2) are forwarded for review and comment. Request recommendation for approval or disapproval be returned to this office with an excerpt from the applicable directive within ten working days from date of receipt. Recommendation for disapproval should be accompanied by a written rationale.


2. This office will forward proposals recommended for approval directly to the Commanding General for decision. Proposals recommended for disapproval will be reviewed by the Model Installation Steering Committee prior to forwarding to the Commanding General.

3. It is recommended that any other Marine Corps Base department that may be affected by the approval or disapproval of the enclosed proposals be contacted during your review.

4. BOSMAD POC is D. Martin, 5521/1577.

HE Smit H. F. SMITH





FORWARD COMPLETED PROPOSAL TO AC/S, BOSMAD, MCB	JICEET
TITLE OR SUBJECT OF PROPOSAL	PROPOSAL NUMBER
Hydrostatic Testing of Unfired Pressure Vessels	87-CLNC-045-FAC
NAME, TITLE, GRADE/RANK, UNIT OF SUBMITTER(S) Donald R. Gurganus, Transportation General Foreman, WS-13,	РНОМЕ 451-5909

Heavy Equipment Unit

CURRENT PROCEDURE

Unfired Pressure Vessels, Air Compressors, are inspected on Marine Corps Base and New River Air Station in accordance with NAVFAC MO-324. They also have been and are hydrostatic tested at regular frequencies. The majority of this equipment has a working pressure from 15-250 psi.

PROPOSED PROCEDURE (If a directive/order must be waived to implement proposal-Identify the specific reference.) Request a waiver of NAVFAC MO-324 and abide by regulations as set forth in OSHA Safety and Health Standards, 29 CFR 1910, General Industry, Revised 11 March 1983, section 1910.169.

## BENEFITS/ADVANTAGES

Benefits and advantages would not require the internal nor the hydrostatic test. There are a minimum of 104 Air Receivers located on Marine Corps Base and New River Air Station. Significant amount of time is required to disassemble the plumbing, fill with water and to test these Air Receivers internally and hydrostatically. After the test has been conducted the plumbing has to be reconnected for use. This procedure in the past has required the assistance of the Tester/Inspector, Plumber, and an Electrician. While this test is in progress the using unit is unable to use the equipment until the test has been completed.

TWE UNDERSTAND THAT THE ACCEPTANCE OF A CASH AWARD FOR THE USE OF THIS PROPOSAL BY THE UNITED STATES GOVERNMENT SHALL NOT FORM THE BASIS OF A FURTHER CLAIM OF ANY NATURE UPON THE UNITED STATES BY ME (US), MY (OUR) HEIRS. OR ASSIGNS.


anua 2-2-87 (SIGNATURE AND DATE)

(SIGNATURE AND DATE)

MODEL INSTALLATION PROPOSAL

**Excellent Installations** — The Foundation Of Defense

ENCL (1)



2 2 OCT 1987

Deputy Base Maintenance Officer

Assistant Chief of Staff, Facilities

MIP PROPOSAL 87-CLNC-045-FAC, HYDROSTATIC TESTING OF UNFIRED PRESSURE VESSELS

Ref: (a) Your memo 11800 FAC of 15 Oct 87

Encl: (1) BMO memo 11800 MAIN of 11 Mar 87

1. The reference requested review and comments on the subject MIP. This MIP has already undergone review and comments were forwarded by memo on 11 March of this year. A copy of that memo is provided as the enclosure.


11800 MAIN

C. G. POWELL

and have a first of the second s

# WRITER: C. G. POWELL, X2511 TYPIST: C. KOWALSKI, 21 OCT 87


where the second s



		EVALUATION POIN	ITS	SCORE
1. LIKELIHOOD OF ACCIDENT BEFORE IMPROVEMENT WAS INSTALLED:				
(a) Exposure frequency	) Slight :	3 Appreciable	6 X Considerable 9	7
(b) No. employees exposed (	Less than 5	3 5 to 25	6 X Over 25 9	7
(c) Possibility of accident (	Unlikely	3 Probable	6 X Very likely 9	7
2. EXTENT OF APPLICATION:	)	9 1	8 27	1 -
(a) Number of locations or area covered	One or two machines, tools, or operations in one shop or office	A group of machines, tools, or operations in a shop or office	General application throughout a large activity	2
3. DEGREE OF HAZARD:	)	9 1	8 27	1
<ul> <li>(a) Extent of possible injury and/or damage to property</li> </ul>	Minor defects or lack of safeguards that may cause non-disabling injury and/or slight damage to property	Major defects or lack of safeguards that may cause disabling in- juries and/or heavy damage to property	Extreme defects or lack of safeguards that may cause a permanent injury or fatality and/or ex- tensive damage to property	10
4. EFFECTIVENESS OF IMPROVEMENT:	0	9 1 1	8 27 1 1	
(a) To what extent will the improvement reduce the possibility of an accident?	Minimizes the hazard slightly	Appreciably limits the hazard or the effects of the hazard	Eliminates the haz- ard, or possibility of disabling injury, or damage to property	10
			TOTAL SCORE	43

## EVALUATION GUIDE FOR SAFETY IMPROVEMENTS

Enel (1



1 1 MAR 1987

11800 MAIN

Base Maintenance Officer, Marine Corps Base, Camp Lejeune Assistant Chief of Staff, Facilities, Marine Corps Base

# MIP 87-CLNC-045-FAC

1. The heart of the problem is NAVFAC MO-324 that requires an internal inspection of unfired pressure vessels (UPV) not less than once every two years for any tank that has an operating pressure in excess of 15 PSI or a volume of more than five cubic feet. Many of the air compressors aboard Camp Lejeune fall into that requirement but have no openings sufficiently large enough to conduct an internal inspection. Accordingly, NAVFAC MO-325 states a hydrostatic pressure test (fill up with water and pressurize at 1.5 times the maximum working pressure) may be substituted for internal inspection. Hence, we are required to hydrostatically test these unfired pressure vessels because of no means to inspect internally. We concur with the MIP that this is an unnecessary frequency and unnecessary work.

2. It is suggested that the MIP be forwarded to NAVFACENGCOM via our Engineering Field Division (LANTDIV) for review to determine the following:

a. Are there satisfactory techniques for conducting internal inspections on UPV's that have very limited internal access?

b. Can the minimum thresholds (five cubic feet & 15 PSI) for UPV inspection requirements be adjusted upward?


c. Can UPV's in non-utility type applications be completely exempt from inspections? This would typically be shop type air compressors.

3. We feel the MIP has merit, but requires relief from existing Department of Navy directives, specifically NAVFAC MO-324. It is recommended relief be pursued.


C. G. POWELL

Blind copy to: Dir, Ops T. Lanier, P&E D. Gurganus, M&R MIP Files Writer: C. Powell, MAIN, X2511 Typist: S. Schmitz, 09 Mar 87

Encl (/)



ROUTING SLIP 1 6 OCT 1987 ACTION INFOINTIAL BMO DBMO DIR, ADMIN DIR, OPS DIR, M&R DIR, UTIL Haven we already SECRETARY



OPNAV 5216/144A (Rev. 8-81) 5/N 0107-LF-052-2320

**DEPARTMENT OF THE NAVY** 

Memorandum 11800 FAC

OCT 1 5 1987 DATE:

FROM: Assistant Chief of Staff, Facilities, Marine Corps Base, Camp Lejeune TO:

Base Maintenance Officer

SUBJ: MIP PROPOSAL NO. 87-CLNC-045-FAC, HYDROSTATIC TESTING OF UNFIRED PRESSURE VESSELS

Encl: (1) Subject Proposal

> 1. The enclosure is forwarded for review and comment. Comments will include a recommendation for approval or disapproval. Recommendations for disapproval must be accompanied by written rationale.

2. Please return comments to this office NLT 30 October 1987.

icacopoulos irection

## - net 1 5 1987

. 1

1129411 10411

> érekekan cikser es déséki. Percitit es, kotsen sogal fosse, o tegénes Paso Maintanesse Diceses


ALL PROPOSE OF OF BERG-A 3-TAC, BYPESIA C TELLING OF BURIERS FREEDLE VES IL

The second togical (1) significant

1. The one losite is forwarded for newcest and evaluant. Comments still include a transmeriation for gammaral se reapprendly recommendations for fital cover work be appointed by writher rationals.

1. Plana a return company to that occupanties is untoled. 1993.

Podentous V Angeler Fotuet to de



INSTRUCTIONS: 1. COMPLETE ALL INFORMATION REQUESTED. 2. PLEASE PRINT OR TYPE LEGIBLY. 3. USE ADDITIONAL SHEETS IF NECESSARY. 4. FORWARD COMPLETED PROPOSAL TO AC/S, BOSMAD, MCB	DO NOT WRITE IN THIS SPACE DATE RECEIVED 3 Feb 87 PROPOSAL NUMBER 87-CLNC-045-FAC	
TITLE OR SUBJECT OF PROPOSAL Hydrostatic Testing of Unfired Pressure Vessels		
NAME, TITLE, GRADE/RANK, UNIT OF SUBMITTER(S) Donald R. Gurganus, Transportation General Foreman, WS-13, Heavy Equipment Unit	PHONE 451-5909	

CURRENT PROCEDURE

Unfired Pressure Vessels, Air Compressors, are inspected on Marine Corps Base and New River Air Station in accordance with NAVFAC MO-324. They also have been and are hydrostatic tested at regular frequencies. The majority of this equipment has a working pressure from 15-250 psi.

Request a waiver of NAVFAC MO-324 and abide by regulations as set forth in OSHA Safety and Health Standards, 29 CFR 1910, General Industry, Revised 11 March 1983, section 1910.169.

## ENEFITS/ADVANTAGES

Benefits and advantages would not require the internal nor the hydrostatic test. There are a minimum of 104 Air Receivers located on Marine Corps Base and New River Air Station. Significant amount of time is required to disassemble the plumbing, fill with water and to test these Air Receivers internally and hydrostatically. After the test has been conducted the plumbing has to be reconnected for use. This procedure in the past has nequired the assistance of the Tester/Inspector, Plumber, and an Electrician. While this test is in progress the using unit is unable to use the equipment until the test has been completed.


UNDERSTAND THAT THE ACCEPTANCE OF A CASH AWARD FOR THE USE OF THIS PROPOSAL BY THE UNITED STATES GOVERNMENT SHALL NOT THE BASIS OF A FURTHER CLAIM OF ANY NATURE UPON THE UNITED STATES BY ME (US), MY (OUR) HEIRS, OR ASSIGNS.

12-2-81 ane (SIGNATURE AND DATE)

(SIGNATURE AND DATE)

MEDEL INSTALLATION PROPOSAL

**Excellent Installations — The Foundation Of Defense** 



15000 87-045

1 1 MAR 1987

11800 MAIN

Base Maintenance Officer, Marine Corps Base, Camp Lejeune Assistant Chief of Staff, Facilities, Marine Corps Base

### MIP 87-CLNC-045-FAC

1. The heart of the problem is NAVFAC MO-324 that requires an internal inspection of unfired pressure vessels (UPV) not less than once every two years for any tank that has an operating pressure in excess of 15 PSI or a volume of more than five cubic feet. Many of the air compressors aboard Camp Lejeune fall into that requirement but have no openings sufficiently large enough to conduct an internal inspection. Accordingly, NAVFAC MO-325 states a hydrostatic pressure test (fill up with water and pressurize at 1.5 times the maximum working pressure) may be substituted for internal inspection. Hence, we are required to hydrostatically test these unfired pressure vessels because of no means to inspect internally. We concur with the MIP that this is an unnecessary frequency and unnecessary work.

2. It is suggested that the MIP be forwarded to NAVFACENGCOM via our Engineering Field Division (LANTDIV) for review to determine the following:

a. Are there satisfactory techniques for conducting internal inspections on UPV's that have very limited internal access?

b. Can the minimum thresholds (five cubic feet & 15 PSI) for UPV inspection requirements be adjusted upward?

c. Can UPV's in non-utility type applications be completely exempt from inspections? This would typically be shop type air compressors.

3. We feel the MIP has merit, but requires relief from existing Department of Navy directives, specifically NAVFAC MO-324. It is recommended relief be pursued.

C. G. POWELL

Blind copy to: Dir, Ops T. Lanier, P&E D. Gurganus, M&R MIP Files Writer: C. Powell, MAIN, X2511 Typist: S. Schmitz, O9 Mar 87

